

Ferrotec Nord Corp.

PRODUCT GENERAL SPECIFICATION

Last update: January 01, 2016

ONE-STAGE MICROMODULES

TYPE	BASIC CHARACTERISTICS, Th=25 °C, VACUUM ENVIRONMENT				DIMENSIONS, mm		
	I _{max} , A	U _{max} , V	Q _{max} , W	ΔT _{max} , °C	Cold side	Hot side	Height
TM-18-0.6-1.2	1.2	2.0	1.5	72	6.0 x 6.0	6.0 x 8.1	2.6
TM-32-0.6-1.2	1.2	3.63	2.7	72	8.0 x 8.0	8.0 x 10.0	2.6
TM-18-0.6-1.5	1.5	2.1	1.83	72	6.0 x 6.0	6.0 x 8.1	2.65
TM-32-0.6-1.5	1.5	3.6	3.4	72	8.0 x 8.0	8.0 x 10.0	2.6
TM-23-0.6-2.0	2.0	2.6	3.2	72	6.0 x 8.2	6.0 x 8.2	1.65
TM-29-0.6-2.0	2.0	3.3	4.0	72	6.0 x 10.2	6.0 x 10.2	1.65
TM-31-0.6-2.2	2.2	3.6	4.6	73	8.0 x 8.0	8.0 x 8.0	2.58
TM-32-0.6-2.2	2.2	3.7	4.7	73	8.0 x 10.0	8.0 x 10.0	2.58
TM-35-0.7-2.8	2.8	4.3	6.65	72	6.0 x 12.2	6.0 x 12.2	1.7
TM-18-0.6-5.5	5.5	2.1	6.8	73	8.7 x 6.8	5.0 x 5.0	1.5
TM-18-0.26-1.0	1.0	2.0	1.2	68	2,74x2,74	2,74x4,0	0,84
TM-9-0.3-0.9	8.0	1.0	0.55	68	1.4x3.0	1.4x3.2	1.1